

F55

FEITIAN

Duo POS



Android 14



4G+2G
Wi-Fi 6: 2.4GHz
Bluetooth 5.2



3.2" LCM + 2.0" LCD
Camera: 0.3MP FF



F

FEITIAN

5

5 Functions: NFC, IC, KEYPAD, QR, SPEAKER

5

5 Colors: Sea Blue | Sunny Yellow | Blue Gray | Pastel Pink | Tangerine Tango



Retail



Supermarket



Restaurant



Hotel



Parking lot



Gas station

	Duo POS	Softpos Version	MPOS Version
Operating System	Android 14	Android 14	Android 14
Processor	Quad-Core 4*A53@2.0GHz	Quad-Core 4*A53@2.0GHz	Quad-Core 4*A53@2.0GHz
Memory	1GB + 8GB (Optional: 2GB+16GB)	2GB + 16GB (Optional: 3GB+32GB)	1GB + 8GB (Optional: 2GB+16GB)
Communications	4G CAT1(LTE-FDD/LTE-TDD) + 2G(GSM) Optional: 4G CAT4(LTE-FDD/LTE-TDD) + 2G(GSM) Wi-Fi 6: 2.4GHz, Bluetooth 5.2	4G CAT1(LTE-FDD/LTE-TDD) + 2G(GSM) Optional: 4G CAT4(LTE-FDD/LTE-TDD) + 2G(GSM) Wi-Fi 6: 2.4GHz, Bluetooth 5.2	4G CAT1(LTE-FDD/LTE-TDD) + 2G(GSM) Optional: 4G CAT4(LTE-FDD/LTE-TDD) + 2G(GSM) Wi-Fi 6: 2.4GHz, Bluetooth 5.2
Location	GPS, BDS, GLONASS	GPS, BDS, GLONASS	GPS, BDS, GLONASS
Main Display	3.2 inch, 240*320 Pixel, IPS LCD, Two Point-touch	3.2 inch, 240*320 Pixel, IPS LCD, Two Point-touch	NA
Sub Display	2.0 inch, 128*32 Pixel	NA	2.0 inch, 128*32 Pixel
Camera	Front Camera: 0.3MP FF, Support Scanner 1D&2D code, Optional 2MP FF	Front Camera: 0.3MP FF, Support Scanner 1D&2D code, Optional 2MP FF	NA
Battery	3.7V/2600mAh	3.7V/2000mAh	3.7V/1200mAh
NFC	13.56MHz, ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card, card emulation	13.56MHz, ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card, card emulation	13.56MHz, ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare card, card emulation
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2	NA	ISO/IEC 7816, Conform to EMV L1/L2
Keys/Buttons	Power Key 16 Keys: 0 ~ 9 Enter Cancel Clear Power Up Down Touch Button: Menu, Home, Back	Power Key Touch Button: Menu, Home, Back	Power Key 16 Keys: 0 ~ 9 Enter Cancel Clear Power Up Down
Peripheral Ports	Type C*1, Support OTG	Type C*1, Support OTG	Type C*1, Support OTG
Card Slot	SIM(Nano)*1, PSAM(Nano)*1, Optional eSIM(Only 4G CAT4)	SIM(Nano)*1, PSAM(Nano)*1, Optional eSIM(Only 4G CAT4)	SIM(Nano)*1, PSAM(Nano)*1
Audio	1W	3W	1W
Adapter	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/1.0A	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/1.0A	Input: 100-240V AC, 50/60Hz 0.35A Output: 5.0V DC/1.0A
Physical	106mm x 76.8mm x 27.5mm	106mm x 76.8mm x 27.5mm	106mm x 76.8mm x 27.5mm
Weight	179g	173g	172g
Environment	Operating Temperature: -10°C ~ 50°C (14°F~122°F) Storage Temperature: -20°C ~70°C (-4°F~158°F) Relative Humidity: 5%~96% (Non-Condensing)	Operating Temperature: -10°C ~ 50°C (14°F~122°F) Storage Temperature: -20°C ~70°C (-4°F~158°F) Relative Humidity: 5%~96% (Non-Condensing)	Operating Temperature: -10°C ~ 50°C (14°F~122°F) Storage Temperature: -20°C ~70°C (-4°F~158°F) Relative Humidity: 5%~96% (Non-Condensing)
Accessories	Adapter*1, USB Cable (only charging)*1, Manual*1	Adapter*1, USB Cable (only charging)*1, Manual*1	Adapter*1, USB Cable (only charging)*1, Manual*1
Certifications	PCI 7.X, EMV L1&L2, EMV CL L1, Amex, payWave, PayPass, Discover, qUICS, MIR, JCB, AuspayNET, EFT POS, RUPAY (base 3.2), WEEE, ROHS, CB, BIS, CE, TQM, WPC, NTRA, GSMA, UN38.8+MSDS	WEEE, ROHS, CB, BIS, CE, TQM, WPC, NTRA, GSMA, UN38.8+MSDS, GMS	PCI 7.X, EMV L1&L2, EMV CL L1, Amex, payWave, PayPass, Discover, qUICS, MIR, JCB, AuspayNET, EFT POS, RUPAY(base 3.2), WEEE, ROHS, CB, BIS, CE, TQM, WPC, NTRA, GSMA, UN38.8+MSDS

