

FLYTECH

POS617N4

Ultra-Narrow Bezel Touch POS with Swivel Stand


Windows Linux Android



Key Features:

- Powered by Intel® Alder Lake-N and Meteor Lake processors
- Supports Windows, Linux, and Android operating systems
- 15.6" display with the world's narrowest 3.95mm touch bezel
- 180° swivel stand design for left and right rotation
- Easy-access motherboard box for simplified service and expansion
- Flexible peripheral support for enhanced functionality

Dimensions



Specifications

		G35	G75U
System	Motherboard	G35	G75U
	Processor	Intel®Alder Lake N: N97, i3-N305	Intel®Meteor Lake Core Ultra 5 125U
	Memory	8GB DDR4 (up to 16GB)	8GB DDR5 (up to 16GB)
	Storage	128GB SSD M.2 (up to 256GB)	128GB SSD M.2 (up to 256GB)
Expansion	M.2 (E Key)	1	1
Display	Size and Resolution	15.6" 1920 x 1080	15.6" 1920 x 1080
	Touch Screen	True-Flat PCAP multi-touch	True-Flat PCAP multi-touch
I/O Ports	USB Type-A	2 x USB3.0 4 x USB2.0	4 x USB3.0 2 x USB2.0
	USB Type-C	1 x USB3.0 full-functioned (DP/PD 5V/3A, 12V/3A)	1 x USB3.0 full-functioned (DP/PD 5V/3A, 12V/3A)
	FeDP	2 x Flytech proprietary miniDP (1 x for main display, 1 x for 2nd display)	2 x Flytech proprietary miniDP (1 x for main display, 1 x for 2nd display)
	Serial Port	3 x RJ48 (standard RS232) (default 0V; 5V, 12V)	3 x RJ48 (standard RS232) (default 0V; 5V, 12V)
	LAN	1 x RJ45	1 x RJ45
	Cash Drawer	1 x RJ11	1 x RJ11
	DC Jack	1 x 4PIN (with latch)	1 x 4PIN (with latch)
	Optional I/O Port	Powered USB	2 x Powered USB 12V 1 x Powered USB 24V
Audio	Internal Speaker	1 x 3W (Option)	1 x 3W (Option)
Indicator	Power Button	1	1
Power	Power Adapter	65W/19V (120W/19V with 2x PUSB 12V & 1x PUSB 24V)	120W/19V
Communication	WLAN + BT	802.11 series + BT5.2 (Option)	802.11 series + BT5.2 (Option)
Peripheral (option)	MSR	3-Track MSR (USB)	3-Track MSR (USB)
	Fingerprint	Fingerprint Reader (USB)	Fingerprint Reader (USB)
	iButton	iButton (USB)	iButton (USB)
	NFC	NFC Reader (USB) (*project-based)	NFC Reader (USB) (*project-based)
	Scanner	2D Scanner (USB) (*project-based)	2D Scanner (USB) (*project-based)
	Customer Display	LCM Display 2 x 20 characters (USB)	LCM Display 2 x 20 characters (USB)
	2nd Display	11.6" 2nd Display (with touch) 11.6" 2nd Display (without touch)	11.6" 2nd Display (with touch) 11.6" 2nd Display (without touch)
Certificate	EMC & Safety	FCC Class A, CE Mark, LVD	FCC Class A, CE Mark, LVD
Environment	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing
Dimensions	W x H x D	356 x 380 x 200 mm (14" x 15" x 7.9")	356 x 380 x 200 mm (14" x 15" x 7.9")
Weight	Weight	5 kg	5 kg
OS Supported		Windows 10 IoT Enterprise, Linux, Android 13.0	Windows 10 IoT Enterprise, Linux, Android 13.0

* PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE *

Taiwan - Headquarters

No.168, Sing-ai Rd., Neihu District,
Taipei City 11494, Taiwan, R.O.C.
886-2-8791-4988
886-2-8791-4966
sales@flytech.com
www.flytech.com

U.S.A. - California

271 East Brokaw Road, San Jose,
CA 95112, U.S.A.
1-510-257-5180
1-510-257-5181
sales.americas@flytech.com

China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,
Shanghai 200233, P.R.China
86-21-5426-1555
86-21-5426-1001
sales@flytech.com.cn
www.flytech.com.cn

China - Hong Kong SAR

Rm01, 6/F, Blk A, Tonic Industrial Centre,
26 Kai Cheung Road, Kowloon Bay,
Kowloon, Hong Kong.
852-3525-5800
852-2751-7447
sales@flytech.com.hk

